

# DMS-18B LOCAL MANIPULATOR

The DMS-18B control panel is used for local operation of the electronic siren. It enables the dispatcher to quickly manage the electronic siren via a keyboard to operate the siren function and an additional microphone connected.

## ADVANTAGES AND FEATURES

### TURNING ON THE SIREN

The control panel has the ALARM function, which is used to immediately start the siren.

### SIREN TEST

The control panel has a TEST function that allows you to run the siren test function.

### RUNNING MACROS

DMS-18B allows to run 8 different alarms stored in the siren memory (pre-programmed) in the GSE-24 or PC-550 module (depending on the DSE siren configuration).

### CONTINUOUS SIREN OPERATION

DMS-18B panel control are powered by an electronic siren. In the event of a 230V power supply failure, the panel still works allows to the siren batteries.

### FORWARDING MESSAGES

The desk microphone connected to the control panel (Jack socket) allows the dispatcher can transmit any voice messages via the electronic siren.

### EXTERNAL SOURCE AUDIO

The DMS-18B allows to connect an external audio source, eg. a wave file from a computer (Jack socket).



## DATA SHEET

<b>Power supply</b>	24 V +/- 3 V (Power for DSE)
<b>Power consumption in stand by</b>	6 mA
<b>Power consumption at work</b>	12 mA
<b>Communication with DSE</b>	4 pair shielded cable (max. 50 m) FTP is suitable
<b>Truck audio</b>	Jack socket
<b>Material</b>	plastic ABS
<b>Dimensions</b>	32 h. x 125 l. x 150 d. mm
<b>Weight</b>	350 g
<b>Warranty</b>	24 months

